


Hollinbrow Steel Size Range - Shim and Foil



Thickness	Thickness Tolerance (6)	Length & Width								
		5m 10mm	5m 12.7mm	5m 25mm	5m 50mm	1m 100mm	1m 150mm	1m 300-305mm	1m 600-625mm	1m ca 1000mm
0.025mm	+/-0.015mm							* (2)		
0.030mm	+/-0.003mm		* (1)	* (1)	* (1)					
0.040mm	+/-0.003mm		* (1)	* (1)	* (1)					
0.050mm	+/-0.003mm		* (1)	* (1)	* (1)		* (1)	* (2)		
0.060mm	+/-0.003mm		* (1)	* (1)	* (1)		* (1)			
0.070mm	+/-0.004mm		* (1)	* (1)	* (1)		* (1)			
0.075mm	+/-0.004mm							* (2)		
0.080mm	+/-0.004mm		* (1)	* (1)	* (1)		* (1)			
0.090mm	+/-0.004mm		* (1)	* (1)	* (1)		* (1)			
0.100mm	+/-0.004mm		* (1)	* (1)	* (1)		* (1)	* (1,2)		
0.120mm	+/-0.004mm		* (1)	* (1)	* (1)		* (1)			
0.127mm	+/-0.0065mm						* (1)	* (2)		
0.150mm	+/-0.005mm		* (1)	* (1)	* (1)		* (1)	* (1,2)		
0.180mm	+/-0.005mm		* (1)	* (1)	* (1)		* (1)			
0.200mm	+/-0.006mm		* (1)	* (1)	* (1)		* (1)	* (1,2)		
0.250mm	+/-0.007mm		* (1)	* (1)	* (1)		* (1)	* (1,2)		
0.300mm	+/-0.007mm		* (1)	* (1)	* (1)		* (1)	* (1)		
0.350mm	+/-0.008mm		* (1)		* (1)		* (1)	* (1)		
0.400mm	+/-0.009mm		* (1)	* (1)	* (1)		* (1)	* (1)		
0.450mm	+/-0.009mm		* (1)		* (1)		* (1)			
0.500mm	+/-0.010mm		* (1)	* (1)	* (1)		* (1)	* (1,2)		
0.550mm	+/-0.010mm		* (1)							
0.600mm	+/-0.010mm		* (1)		* (1)			* (1)		
0.650mm	+/-0.012mm		* (1)							
0.700mm	+/-0.012mm		* (1)		* (1)			* (1)		
0.750mm	+/-0.012mm		* (1)							
0.800mm	+/-0.013mm		* (1)		* (1)			* (1)		
0.850mm	+/-0.013mm		* (1)							
0.900mm	+/-0.013mm		* (1)		* (1)			* (1)		
0.950mm	+/-0.013mm		* (1)							
1.000mm	+/-0.018mm		* (1)	* (1)	* (1)			* (3)		
1.500mm	+/-0.022mm							* (3)		
2.000mm	+/-0.028mm							* (3)		

* = All available sizes

 = Next day delivery available

(1) = High Carbon C100S / CS100 / SAE1095 Hardened & Tempered

(2) = Mild Steel CS4 / DC01 / SAE1008-10

(3) = available in CS80 / 75Cr1 / SAE1075 Hardened & Tempered